



BWSET_121_2KFD_1R1TB

1x BWNVR-2411P | 1x HDD-1000HV | 2x BWNC-241FDIF
 1x BWNVR-2411P | 1x HDD-1000HV | 2x BWNC-241FDIF

PRODUCT DESCRIPTION

► Application:

The IP-cameraset consists of the SANTEC 2 megapixel camera SNC-211RLNA with 30x motorzoom and the weather proof housing HEL-62D. 2 meter connection cable is included.

► Technical specifications:

Recorder	BWNVR-2411P
Type	Network videorecorder
Decoding / Display / Performance	>>Decoding / Display / Performance<<
Compression (video)	H.264 / H.265 / MJPEG / MPEG-4
Compression (audio)	AAC, G.711, G.726
Max. resolution	UHD (8 MP)
Bit Rate per channel	16Kbps - 20Mbps
IP video channels (active)	4
Decoding 4x view (max)	1x 8MP or 4x 2MP (1080p)
Internal operating system	Embedded LINUX
Features	>>>>>>>>>FEATURES<<<<<<<<<<<<<<
Motion detection	Yes, from camera
Camera occlusion detection	Yes, from camera
Lost signal detection	Yes
Intelligent Video Analysis (IVA)	Yes (depends on camera model)
Motion recording	Yes
Manual recording	Yes
Permanent recording	Yes
Schedule recording	Yes
IVA recording	Yes

SANTEC BW AG
 Wormgermühle, 58540 Meinerzhagen, Germany
 Tel.: +49 2358 905 450, Fax: +49 2358 905 499
 info@santec-video.com, www.santec-video.com



Our products undergo constant development. Please refer to the price list for our most up-to-date product program. Errors and omissions excluded. No responsibility accepted for accuracy of images.

► Technical specifications:

Pre-alarm recording	Ja, einstellbar bis zu 30 S.
Post-alarm recording	Yes, adjustable up to 300 s.
Snapshot notification	Yes
Push-Notification	Yes via mobile App. (Pro version!)
Intelligent search criteria	Depends on camera
Watermark	Yes
Password protection	Yes
Log files	Yes
Live picture	Yes
4K camera support	Yes
Dsisplay split	1/4/8
Two man rule	Yes
Delete images automatically	Yes
Interface	>>>>>>>>>INTERFACE<<<<<<<<<<<<<<
Audio inputs	1 x Cinch
Audio outputs	1 x Cinch
Max. HDD capacity	6 TB
Max. number of HDDs (internal)	1 x SATA III
External HDD possible	through USB
USB interface	1 xUSB 2.0, 1 x USB 3.0
USB ports	1 x Front, 1 x Backside
Monitor outputs	1x HDMI (UHD 3840x2160), 1x VGA (FullHD 1920x1080)
Spot monitor outputs	No, simultaneos output HDMI/VGA
Number of supported monitors	1
Export interface	USB/network
Network	>>>>>>>>>NETWORK<<<<<<<<<<<<<<
Number of PoE ports	4
Number of Ethernet ports	4x PoE + 1x LAN
Ethernet connector	RJ-45
Ethernet standards	10/100/1000 Base-T
PoE standard	IEEE802.3at / IEEE802.3af
Power consumption to PoE standard IEEE802.3af	15,4 watt /channel
Power consumption to PoE standard IEEE802.3at	25,4 watt single port
Max. PoE Output Voltage (port)	max. 50 W gesamt
Remote	>>>>>>>>>REMOTE<<<<<<<<<<<<<<
P2P support	Yes
Time synchronisation	NTP protocol
DHCP support	Yes
FTP support	Yes
Supported protocols	HTTP,TCP,UDP, DHCP,SMTP,UPnP,NTP, IPv4, IPv6, RTSP
Supported software standards	ONVIF, CGI
Remote connections	Yes

SANTEC BW AG
 Wormgermühle, 58540 Meinerzhagen, Germany
 Tel.: +49 2358 905 450, Fax: +49 2358 905 499
 info@santec-video.com, www.santec-video.com



► Technical specifications:

Operating temperature (°C)	-30 to +60
Storage temperature (°C)	-30 to +60
Rel. humidity (%)	Max. 95, non-condensing
Dimensions DxH (mm)	81 mm x F109.9 mm
Weight	350 g
Identifier	CE, RoHS
Items included in delivery	Installation material, quickguide
Festplatte	1TB Video Surveillance HDD

► Note:

Set Artikel Detaillierte Informationen entnehmen Sie bitte dein einzelnen Artikeln

► Recommended Accessories

SML-2212	SANTEC 22" CCTV 6 in 1 plastic-monitor, 1920x1080, 60Hz, CVBS,CVI,TVI,AHD,VGA,HDMI
SNPS-12D2	SANTEC stabilized power supply 12 V DC, 1.5 A, plug
SNCA-MK-136	Adapter / mounting kit for BURGcam DOME 303
SNCA-RD-PFA200W	Rain shade for SANTEC dome cameras