



HDMI-700-E

HDMI Extender
Transmission via UTP up to 60m

PRODUCT DESCRIPTION

► Application:

Übertragung von FullHD (1080p) HDMI Signalen über CAT6 Kabel bis zu 50m. Die Übertragung von IR-Signalen ins unidirektional möglich. HDMI Signal kann am Sender über den HDMI Loop Ausgang lokal verwendet werden. Verbessertes Anti-Static und Anti-Interferenz Schutz für hohe Performance.

► Technical specifications:

| | |
|-------------------------------|--|
| Type | Repeater |
| Input Signal | HDMI |
| Relay Output | HDMI |
| Transmission mode | Twisted-pair (RJ-45) |
| max. linkdistance | 50 m (CAT 6, DC Impedanz < 9.5Ohm/100m) |
| HDCP Version | Support HDCP 1.2 |
| HDMI Version | Support 1.3 and lower versions |
| More resolutions | 1080p / 1080i / 720p / 720i / 576p / 576i / 480p |
| Voltage | 5 V DC |
| Max. Power consumption (watt) | 3W |
| Housing material | Aluminium |
| Housing colour | Black |
| Dimensions WxHxD (mm) | 79.5mmx68mmx16.5mm |
| Weight | 133g |
| Operating temperature (°C) | -10 - 55°C |
| Rel. humidity (%) | Max. 95, non-condensing |
| Items included in delivery | 1x Transmitter, 1x Receiver, 1x power supply |
| Specials | Transmission HDMI signal via UTP cabel |

BURG-GUARD GmbH
Wormgermühle, 58540 Meinerzhagen, Germany
Tel.: +49 2358 905 490, Fax: +49 2358 905 499
BURG-GUARD@burg.biz, www.burg-guard.com



► Technical specifications:

MTBF

>5000h

► Weitere Bilder:

