



M-500AK-10

10 x Kompakt-Balune für ein Videosignal, Sender
o. Empfänger, 1xBNC-Buchse, 1xJ-45-Buchse

PRODUCT DESCRIPTION

► Application:

A passive, very compact balun for video signal transmission via twisted pair cable. This unit can be used as transmitter or receiver. The max. distance is 600 m depending on cable type. up to 200m when the power should be transferred.

► Technical specifications:

| | |
|------------------------------------|---|
| Type | Videobalun, passive |
| Video input/output | 1 x BNC 1 Vpp |
| Twisted pair input/output | 1 x RJ-45 connector |
| Max. cable length twisted pair (m) | 300 |
| Transmission of | Video, Power (24 V AC / 12 V DC) |
| Adjustable video level | no |
| Housing material | Plastic |
| Housing colour | Black |
| Voltage | None |
| Operating temperature (°C) | 0 to +50 |
| Dimensions WxHxD (mm) | 69 x 25 x 20.7 mm |
| Weight | 30 g |
| Identifier | CE |
| Specials | Power can be transferred by using an opt. power sup |

► Note:

BURG-GUARD GmbH
Wormgermühle, 58540 Meinerzhagen, Germany
Tel.: +49 2358 905 490, Fax: +49 2358 905 499
BURG-GUARD@burg.biz, www.burg-guard.com



Our products undergo constant development. Please refer to the price list for our most up-to-date product program. Errors and omissions excluded. No responsibility accepted for accuracy of images.

Please note: The connector of this balun is not compatible with the SANTEC UTP system technology. To use it together with the SANTEC UTP system technology, please use the video balun VTUD-1.