



SCC-221KDNM

SANTEC HD-CVI Full HD dome camera
2,8 - 11 mm, manual vario lens, IP-44

PRODUCT DESCRIPTION

► Application:

SANTEC day/night HD-CVI dome camera for indoor applications.

► Technical specifications:

Type	Day/Night Dome camera
Video signal	HD-CVI, CVBS (analogue)
Sensor	1/2.9" CMOS
Sensor type	1/2.9" Progressive Scan CMOS
Horizontal resolution (TVL)	1080p / 720p
Effective pixel	1920x1080
Signal processing	Digital (DSP)
Synchronisation	Intern
Lens type	Built-in manual vario lens
Focal length	2.8 - 11 mm / F1.4
Angle of view (horizontal)	103° - 22° (HD-Mode)
IR cut filter	IR-Cut filter (mechanical)
Sensitivity (Lux)	0.05 Lux (color)
Automatic gain control (AGC)	AGC
Digital noise reduction (DNR)	2NR / 3DNR
Shutter (sec.)	1/3 - 1/100,000
Video output	BNC, 75 Ohm 1 Vpp
Vandal-proof	No
Housing colour	White
Housing material	Plastic

BURG-GUARD GmbH
Wormgermühle, 58540 Meinerzhagen, Germany
Tel.: +49 2358 905 490, Fax: +49 2358 905 499
BURG-GUARD@burg.biz, www.burg-guard.com



► Technical specifications:

Integrated IR-LEDs	No
Voltage	12 V DC / 24 V AC
Max. Power consumption (watt)	1.1
Operating temperature (°C)	0 to +45
Rel. humidity (%)	Max. 95, non-condensing
Dimensions DxH (mm)	128 x 90
Weight	270 g
Identifier	CE, RoHS
Specials	Coaxtransmission up to 700m

► Note:

Caution: This camera must not be powered with multi-power supply adapters.

► Recommended Accessories

KOAX-0.6/100	Coaxl cable 0.6/3.7, 75 Ohm for indoor usage, 100 m ring
SNPS-12D2	SANTEC stabilized power supply 12 V DC, 1.5 A, plug