

NUUO®



SCB-A08

Ethernet I/O Box
fits to NUUO systems

PRODUCT DESCRIPTION

► Application:

SCB-A08 is an I/O box to intermediate the communication between a surveillance server and multiple peripherals. It joins up all the major components in your surveillance network to deliver your prospective management and protection over your property.

► Technical specifications:

Type	Ethernet I/O-Box
Input	8
Output	8x relay-output, RS-485, RS-422, RS-232
Relay type (output)	Subminiature Relay
Max. switching voltage	250VAC / 30VDC
Max. switching current	5A
Max. switching power	1250VA / 150W
Interfaces	LAN, RS-485, RS-422, RS-232
Baud rate	Serial 1: 9600, Serial 2: 115200
Data bits	5, 6, 7 or 8
Stop bits	1, 1.5 or 2
Parity	None, Even, Odd, Mark, Space
Voltage	12 V DC - 30 V DC
Max. Power consumption (watt)	max. 15
Operating temperature (°C)	0 to 70
Rel. humidity (%)	Max. 90, non-condensing
Dimensions WxHxD (mm)	114 x 143 x 28
Weight	300 g

BURG-GUARD GmbH
Wormgermühle, 58540 Meinerzhagen, Germany
Tel.: +49 2358 905 490, Fax: +49 2358 905 499
BURG-GUARD@burg.biz, www.burg-guard.com



Our products undergo constant development. Please refer to the price list for our most up-to-date product program. Errors and omissions excluded. No responsibility accepted for accuracy of images.

► **Technical specifications:**

Compatible with	MMainconsole, NVRmini 2, NVRsolo, Titan, Crystal
Identifier	CE, FCC