



SNVR-36444E

SANTEC 4K/H.265 network video recorder, 64-ch
16xPoE, respectively ch.1-8 with ePoE(without HDD)

PRODUCT DESCRIPTION

► Application:

This network recorder of the SNVR-series has an integrated PoE switch. You will have full flexibility thanks to remote control by using the Burg cam App or the CMS software. The SNVR-2812P is also able to support cameras with 4K/Ultra HD resolution (IP cameras with up to 12 mP (ULtra HD)). Camera updates can conveniently be made by using the USB port on the recorder. Newly added cameras are automatically detected when connected to the PoE port. This will reduce installation efforts. The recorder is P2P/Cloud capable (Burg Cam App and Burg Cam Pro App for iPhone, iPad and Android systems).

► Technical specifications:

Type	Network videorecorder
Decoding / Display / Performance	>>Decoding / Display / Performance<<
Compression (video)	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Compression (audio)	AAC, G.711, G.726
Max. resolution	12 MP (4000x3000)
More resolutions	8MP, 5MP, 3MP, 1080p, 720p, D1
Max. frame rate (fps)	30
Record rate max	320 Mbps
Bit Rate per channel	16Kbps - 20Mbps
IP video channels (active)	64
Decoding 4x view (max)	2x 12MP (20fps) or 4x 8MP (25/30fps)
Decoding 8x view (max)	8x 4MP (25/30 fps)
Decoding 16x view (max)	16x 2MP (25/30 fps)
Decoding 32x view (max)	32x 720P (25/30fps)
Decoding 64x view (max)	64x D1 (25/30fps)
Internal operating system	Embedded LINUX

BURG-GUARD GmbH
Wormgermühle, 58540 Meinerzhagen, Germany
Tel.: +49 2358 905 490, Fax: +49 2358 905 499
BURG-GUARD@burg.biz, www.burg-guard.com



► Technical specifications:

Management of IP devices	Auto / manual
DynDNS support	Yes
UPNP support	Yes
SNMP support	Yes (version 3)
Time synchronisation	NTP protocol
DHCP support	Yes
Multicasting	Yes
FTP support	Yes
Supported protocols	HTTP, TCP, UDP, DHCP, SMTP, UPnP, NTP, IPv4, IPv6, RTSP
Supported software standards	ONVIF, CGI
Remote connections	Yes
Max. remote connections	128
User management	Yes
Menu languages	German, English
Access	Browser / Client SW / Mobile App / local interface
Supported software for remote access	Web PlugIn, BW-IP-CVI-VMS, Burg Cam App
Supported devices	iPhone, iPad, Android
Cloud service	Yes, BURG-WÄCHTER cloud
Preset positions	Depends on camera
PTZ control	Yes
PTZ protocols	PELCO-D, PELCO-P, SAMSUNG, SONY...
General	>>>>>>>>>GENERAL<<<<<<<<<<
Housing colour	Black
Rack mount (U)	2
Noise emission (dB)	<50 (T_amb=-10-30°C)
Max. Power consumption (watt)	NVR: 17,5 (without HDD)
Voltage	100 - 240 V AC
Operating temperature (°C)	-10 to +55
Storage temperature (°C)	-20 to +70
Rel. humidity (%)	10 - 90, non-condensing
Dimensions WxHxD (mm)	411.2 x 76 x 440
Weight	4,7 kg (without HDD)
Identifier	CE, RoHS
Items included in delivery	power cord(EU+GB), remote control, PC-mouse, QIG
Items included in delivery	HDMI+LAN cabel, 4x SATA cable, HDD srews
Items included in delivery	19" Rack-Mount adapter
Specials	Support 4K/UHD cameras, Two man rule

► Note:

Bei der Verwendung eines Digital Rekorders ist der Einsatz einer USV Anlage

BURG-GUARD GmbH
 Wormgermühle, 58540 Meinerzhagen, Germany
 Tel.: +49 2358 905 490, Fax: +49 2358 905 499
 BURG-GUARD@burg.biz, www.burg-guard.com



Our products undergo constant development. Please refer to the price list for our most up-to-date product program. Errors and omissions excluded. No responsibility accepted for accuracy of images.

empfohlen. Dieser Rekorder wird ohne Festplatte ausgeliefert. In der Kategorie "Empfohlenes Zubehör" können Sie eine passende Festplatte wählen. Diese wird dann von unserem Serviceteam kostenfrei für Sie eingebaut.

► Weitere Bilder:



► Recommended Accessories

HDD-1000HV	HDD for DVR/NVR, 1 TB SATA 24/7 tested
HDD-2000HV	HDD for DVR/NVR, 2 TB SATA 24/7 tested
HDD-4000HV	HDD for DVR/NVR, 4 TB SATA 24/7 tested
HDD-6000HV	HDD for DVR/NVR, 6TB SATA 24/7 tested
HDD-10000HV-AI	AI-HDD for DVR/NVR, 10TB SATA 24/7 tested
KSC-USB-NET	USB Keyboard for SCVR und SNVR recorders, analog. and IP domes
SNAEOC-1002-1T	SANTEC single-port-ethernet transmitter over coax cable
SNAEOC-1002	SANTEC passive ethernet over coax converter up to 1000m
SNAEOC-1002-1C	SANTEC single-port-ethernet receiver over coax cable
HDMI-700-E	HDMI Extender Transmission via UTP up to 60m
BURGVMS	VMS for SANTEC BURG-WÄCHTER cameras and recorder
HDD-8000HV	HDD for DVR/NVR, 8TB SATA 24/7 tested
16925	Remote online support price per one hour support
BWNET-12632	Video-Gigabit,24-Port PoE Switch,max.300W af/at 24x10/100Mbps Ethernet, 2xGigabit combo ports
NSW2010-24T2GC-POE	Uniview 24-Port PoE Switch 24x10/100Mbps Ethernet, 2xGigabit combo ports
KVM-HD150	Full HD HDMI extender, Cat5e up to 150m Übertragung per CAT5e/6 bis zu 150m