



## VTC-HDH210FSP

SANTEC vandal-proof color dome camera  
580 TVL, surface/flush mount, 3.0mm lens

### PRODUCT DESCRIPTION

#### ► Application:

The vandal-proof dome camera has specially been developed for applications in public areas such as subway stations, elevators, public parking buildings, banks etc. The camera is designed for surface mount or flush mount.

#### ► Technical specifications:

Type	Day/Night vandal-proof dome camera
Video signal	PAL
Sensor	1/3"
Sensor type	Sony Super HAD CCD Chip
Horizontal resolution (TVL)	580 (color) / 580 (b/w)
Effective pixel	752 (H) x 582 (V)
Signal processing	Digital (DSP)
Synchronisation	Intern
S/N ratio (dB)	> 48 dB
Lens type	Fix lens
Focal length	3 mm / F2.0
Angle of view (horizontal)	77°
IR cut filter	Electronic
Sensitivity (Lux)	0.1 Lux
Automatic gain control (AGC)	AGC
Digital noise reduction (DNR)	Yes
Backlight compensation	BLC
Wide dynamic range (WDR)	No
Day/night mode adjustment	Auto

BURG-GUARD GmbH  
Wormgermühle, 58540 Meinerzhagen, Germany  
Tel.: +49 2358 905 490, Fax: +49 2358 905 499  
BURG-GUARD@burg.biz, www.burg-guard.com



## ► Technical specifications:

Motion detection (zones)	12
Camera title	No
Video output	BNC, 75 Ohm 1 Vpp
UTP (twisted pair)	No
Control interface	No
Classification	IP-66
Vandal-proof	Yes
Housing colour	White
Housing material	Aluminium
Integrated IR-LEDs	No
Voltage	12 V DC
Max. Power consumption (watt)	4
Operating temperature (°C)	-10 to +50
Rel. humidity (%)	30 - 90
Dimensions DxH (mm)	83x70
Weight	400 g
Identifier	CE

## ► Recommended Accessories